

Listing of the Claims:

1. (Previously Presented) A method comprising:
receiving, at a mobile terminal, buffered data as a digital broadcast transmission burst in a time-slicing signal, the buffered data corresponding to a first portion of an information stream, said digital broadcast transmission burst having a duration smaller than the duration of said first portion of said information stream;
powering-up a digital broadcast receiver in the mobile terminal in synchronicity with the transmission of said digital broadcast transmission burst such that the mobile terminal is powered-up when said digital broadcast transmission burst is being received; and
buffering said digital broadcast transmission burst in a receiver input buffer of the digital broadcast receiver.
2. (Previously Presented) A method as in claim 1 wherein the buffered data is transmitted from a service input buffer comprising at least one member of the group consisting of: a first-in-first-out (FIFO) buffer, an elastic buffer, a ring buffer, and a dual buffer having separate input and output sections.
3. (Previously Presented) A method as in claim 1 wherein said buffered data comprises at least one of: a predetermined amount of said information stream and an amount of said information stream received during a predetermined time interval.
4. (Previously Presented) A method as in claim 1 wherein said powering-up said receiver occurs a specified interval of time prior to said receiving.
5. (Original) A method as in claim 4 wherein said specified interval of time comprises a member of the group consisting of: a bit-rate adaptation time, a receiver switch-on time, and a receiver acquisition time.
6. (Cancelled).

7. (Cancelled).

8. (Previously Presented) A method as in claim 1 further comprising powering-down said receiver a predefined interval of time subsequent to said powering-up said receiver.

9. (Original) A method as in claim 8 wherein said predefined interval of time comprises a time interval greater than said duration of said transmission burst.

10. (Cancelled).

11. (Cancelled).

12. (Previously Presented) A method as in claim 1 wherein the buffered data is encapsulated using a multi-protocol encapsulator to form encapsulated data.

13. (Previously Presented) A method as in claim 12 wherein said multi-protocol encapsulator conforms to standard EN 301192.

14. (Previously Presented) A method as in claim 12 further comprising:
obtaining said transmission burst from said receiver input buffer; and
stripping encapsulation from said transmission burst to form received data.

15. (Previously Presented) A method as in claim 14 further comprising sending said received data to an application processor for conversion to an information data stream.

16. (Previously Presented) A method as in claim 1 further comprising:
receiving a second buffered data as a second digital broadcast transmission burst, said second digital broadcast transmission burst having a duration smaller than the duration of said portion of said second information stream, wherein the second buffered data comprises a portion of a second information stream.

17. (Previously Presented) A method as in claim 16 wherein the transmission burst and said second transmission burst are multiplexed to produce a time-division multiplexed signal.

18. (Cancelled).

19. (Currently Amended) An apparatus comprising:

a processor; and

memory configured to store computer readable instructions that, when executed by the processor, cause the processor to perform a method comprising:

receiving buffered data as a digital broadcast transmission burst in a time-slicing signal, the buffered data corresponding to a first portion of an information stream, said digital broadcast transmission burst having a duration smaller than the duration of said first portion of said information stream;

powering-up a digital broadcast receiver in synchronicity with the transmission of said digital broadcast transmission burst such that the apparatus is powered-up when said digital broadcast transmission burst is being received; and

buffering said digital broadcast transmission burst in a receiver input buffer

~~a digital broadcast receiver for receiving at least a first portion of streaming information as a digital broadcast transmission burst;~~

~~means for powering up said digital broadcast receiver at a pre-determined powered-up time, wherein the pre-determined powered-up time is synchronized with the reception of the digital broadcast transmission burst and wherein said pre-determined powered-up time occurs at the setting of a flag indicating an almost-empty byte count in said receiver input buffer;~~

~~a receiver input buffer for storing said transmission burst; and~~

~~means for powering down said digital broadcast receiver at a pre-determined powered-down time.~~

20. (Currently Amended) The apparatus as in claim 19 wherein ~~said pre-determined powered-up time~~ the digital broadcast receiver is powered-up occurs a specified period of time subsequent to ~~said a~~ pre-determined powered-down time.

21. (Cancelled).

22. (Currently Amended) The apparatus as in claim 19 wherein ~~said pre-determined powered-up time~~ the digital broadcast receiver is powered-up occurs an incremental period of time prior to ~~occurrence of said transmission~~ the transmission of the digital broadcast transmission burst.

23. (Previously Presented) The apparatus as in claim 22 wherein said incremental period of time comprises a member of the group consisting of: a bit rate adaptation time, a receiver switch-on time, a receiver acquisition time, and a bit-rate variation time interval.

24. (Currently Amended) The apparatus as in claim 19 wherein the digital broadcast receiver is powered-down ~~said pre-determined powered-down time~~ occurs a specified period of time subsequent to the powering up of the digital broadcast receiver ~~said pre-determined powered-up time~~.

25. (Previously Presented) The apparatus as in claim 24 wherein said specified period is at least as great as said transmission burst duration.

26. (Currently Amended) The apparatus as in claim 19 wherein the digital broadcast receiver is powered-down ~~said pre-determined powered-down time~~ occurs at the setting of a flag indicating an almost-full byte count in said receiver input buffer.

27. (Currently Amended) The apparatus as in claim 19 wherein the digital broadcast receiver is powered-down ~~said pre-determined powered-up time~~ occurs an incremental period of time subsequent to the transmission of said digital broadcast transmission burst.

28. (Currently Amended) The apparatus as in claim 19 further comprising an application processor for converting said digital broadcast transmission burst into an information data stream.

29. (Currently Amended) The apparatus as in claim 19 further comprising a stream filter for stripping ~~said~~ encapsulation from said digital broadcast transmission burst.

30. (Previously Presented) The apparatus as in claim 29 wherein said stream filter comprises an Internet protocol (IP) filter.

31. (Currently Amended) ~~A system~~An apparatus comprising:
a transmitter ~~system for~~configured to broadcast ~~broadcasting~~ at least a portion of streaming information provided by an information service provider as a digital broadcast transmission burst; ~~said transmitter system including a service input buffer; and~~
a service input buffer, wherein
said digital broadcast transmission burst is configured for transmission~~transmitted~~ to a mobile terminal ~~and the transmission of the digital broadcast transmission burst is in~~
synchronicity~~zed~~ with a powering-up of a digital broadcast receiver of the mobile terminal.

32. (Cancelled).

33. (Cancelled).

34. (Currently Amended) The ~~system~~apparatus as in claim 31 wherein at least one service is provided by the information service ~~provided~~provider via at least one information stream.

35. (Cancelled).

36. (Currently Amended) The ~~system-apparatus~~ as in claim 31 wherein at the transmission of the digital broadcast transmission burst is synchronized with the powering-up of the digital broadcast receiver based on a pre-determined powered-up time.

37. (Currently Amended) The ~~system-apparatus~~ as in claim 36 wherein said pre-determined powered-up time occurs an incremental period of time prior to the transmission of said digital broadcast transmission burst.

38. (Currently Amended) The ~~system-apparatus~~ as in claim 36 wherein said pre-determined powered-up time occurs a specified period of time subsequent to said pre-determined powered-down time.

39. (Cancelled).

40. (Currently Amended) The ~~system-apparatus~~ as in claim 31 further comprising an application processor for converting said digital broadcast transmission burst into an information data stream.

41. (Currently Amended) The ~~system-apparatus~~ as in claim 31 wherein the transmitter ~~system further comprises~~ a multi-protocol encapsulator for encapsulating at least a portion of said streaming information.

42. (Currently Amended) The ~~system-apparatus~~ as in claim 41 ~~further comprising an Internet protocol (IP) filter for stripping~~ wherein the encapsulation is removable using an Internet protocol (IP) filter ~~from encapsulated streaming information.~~

43. (Currently Amended) The ~~system-apparatus~~ as in claim 31 ~~wherein the transmitter system further comprises~~ comprising:

a second service input buffer for storing at least an interval of second streaming information provided by a second information service provider, wherein said transmitter ~~system~~ broadcasts the contents of said second service input buffer as a second transmission burst.

44. (Currently Amended) The ~~system apparatus~~ as in claim 43 further comprising a multiplexer for multiplexing said digital broadcast transmission burst and said second transmission burst such that said transmitter ~~system~~ broadcasts said digital broadcast transmission bursts and said second transmission burst as a time-division multiplexed signal.

45. (Currently Amended) The ~~system apparatus~~ as in claim 43 further comprising a network operator input buffer.

46. (Currently Amended) A ~~system comprising~~ method comprising:
receiving streaming information from a service provider; and
transmitting, from a digital broadcast transmitter, said streaming information as a digital broadcast transmission burst to a remote mobile terminal at a higher bit rate than the rate at which said streaming information is received from the service provider, wherein the transmission is synchronized with a powering-up of the remote mobile terminal.

~~a service input buffer for receiving streaming information from a service provider; and~~
~~a digital broadcast transmitter for transmitting said streaming information as digital broadcast transmission bursts to a remote mobile terminal at a higher bit rate than the rate at which said streaming information is received from said service provider, wherein said streaming information is transmitted in synchronization with a powering-up of the remote mobile terminal.~~

47. (Currently Amended) The ~~system method~~ as in claim 46 further comprising a ~~multi-protocol encapsulator for encapsulating the streaming information.~~

48. (Currently Amended) The ~~system method~~ as in claim 46 further comprising:
~~a second service input buffer for receiving second streaming information supplied by a~~
~~second service provider; and~~

| ~~a second multi-protocol encapsulator for encapsulating said second streaming~~
information.

| 49. (Currently Amended) The ~~system-method~~ as in claim 48 further comprising
multiplexing the digital broadcast transmission burst and the second streaming information such
that the digital broadcast transmission burst and the second streaming information are transmitted
as time division multiplexed signals~~a multiplexer~~.

| 50. (Currently Amended) The ~~system-method~~ as in claim 47 ~~further comprising a~~
~~network operator input buffer~~ wherein the digital broadcast transmission burst is transmitted a
predefined period of time prior to the powering-up of the remote mobile terminal.

51. (Cancelled).

52. (Previously Presented) The method of claim 1, wherein the streaming
information comprises multimedia content.

53. (New) The method of claim 46, wherein a size of the digital broadcast
transmission burst is defined independently of a receiver bandwidth allocation.